

QCAM5

The latest addition to the well renowned QCAM camera range

Integrating the latest **cutting-edge technologies** (deep learning-based algorithms), the QCAM5 camera delivers **unprecedented number plate recognition** capabilities. Additionally, its outstanding image resolution and a **unique set of functionalities** designed to provide further **vehicle characterization** makes this product the "best in class" within its category.

The QCAM5 camera can operate on **1, 2, 3 or 4 lanes** and is able to differentiate **all kind of vehicles** (e.g. cars, trucks, busses, motorcycles, bicycles, trailers, etc.), **objects and persons**.


Moreover, it also integrates in option a **"Make & Model"** recognition feature, as well as a **"vehicle colour"** characterization. Both features are invaluable in finding vehicles and closing the current gap in similar product offerings, as these features, when available, typically require additional hardware and software.

The QCAM5 camera is also able to calculate an **instantaneous speed** estimate for each vehicle travelling within its field of view.

The whole QCAM5 camera technology is embedded in a **small footprint** - but well-designed - housing that discretely blends into urban environments. All details have been carefully thought and engineered to facilitate its installation and deployment: a **miniaturized motorization within the support arm** allows **remote alignment**, removing the burden of relying on an aerial lift truck for final mechanical setup. A motorized lens is also incorporated into the system.

MAIN TECHNICAL CHARACTERISTICS

- ▶ 5 MP dual high-sensitivity CMOS sensors
- ▶ Processor: NVIDIA Jetson TX2
- ▶ Vehicle speed detection up to 300 km/h
- ▶ Connectivity: Ethernet, Wi-Fi, 4G, 4G LTE
- ▶ GNSS GPS included
- ▶ Motorized support arm (pan & tilt) VARI-
- ▶ FOCAL 8, 16, 25, 35 mm with P-FOCUS and P-IRIS
- ▶ PSU: 24V DC 2.5A (35W only)
- ▶ Weight: 3.8kg
- ▶ IP67 protection & IK10
- ▶ **Now homologated for Speed Section Control**



Ready to use with

CONTACT US

+32 2 610 15 00
contact@macq.eu

QCAM5	
Overall Performances	
Number of monitored lanes	Up to 4 lanes
Maximum speed of detected objects	Up to 300 km/h
Working distance	Up to 70m (day & night)
Vehicle detection accuracy	>99%
Plate recognition accuracy	>99%
Classification	All vehicle types (incl. cars, trucks, busses, motorcycles, bicycles, trailers, etc.), objects and persons (optional)
Make & model recognition	Yes (optional)
Vehicle colour recognition	Yes (optional)
ADR recognition	Yes (optional)
Instant speed detection	Yes (optional)
Driver attributes: Seatbelt, phone detection, ...	Yes (optional)
Hardware & Connectivity	
2 Sony CMOS sensors IMX 567, Pregius Series (ANPR & context camera)	5 MP
VARIFOCAL	8, 16, 25, 35 mm
P-FOCUS	Yes
P-IRIS	Yes
Infra-red Illuminator	12 Wide angle IR LED with Dome lens 855nm
Storage SSD	256 GB / 512 GB / 1 TB
GNSS	Yes
3G/ 4G/ 4G LTE	Yes (optional)
Wi-Fi, IEEE 802.11a/b/g/n/ac, 2.4/ 5 GHz	Yes
Ethernet RJ45	Yes
Pan & tilt remote control	Yes, via motorized arm
Software & Image Processing	
OS	Ubuntu (Linux For Tegra)
Encryption	AES256
Automatic white balance & backlight attenuation	Yes
Streaming	RTSP, Color & B/W H264
Compression	JPEG
Time	NTP & GNSS synchronization
Communication protocol	Web server & TCP/IP
External triggering	Yes, thanks to a connected I/O controller (optional)
Data transmission	JSON, SNMP, UTM
ONVIF Compatibility	Profile S
System integration	M ³ platform, via SDK (available upon request)
Mechanical & Conformity	
Dimensions	188 x 256 x 270 mm
Weight	3.8 kg
Power supply	24V DC 2.5A (35W only)
Solar panel & battery autonomous power supply	Available upon request
CE conformity	Yes
IP/IK rating	IP67, IK10
Operating temperature	-25°C to +65°C
Operating humidity	10% to 95%